



Material Safety Data Sheet

UNIFOAM

HEALTH	*	2
FLAMMABILITY		1
PHYSICAL HAZARD		0
PERSONAL PROTECTION		

1. Product and Company Identification

Material name	UNIFOAM
Patent Number	Not available
Version No.	3
CAS #	Mixture
Product use	Foamer
Manufacturer information	Clearwater International L.L.C. 100 Leetsdale Industrial Drive Leetsdale, PA 15056 US CHEMTREC 1-800-424-9300/703-527-3887
Emergency	CHEMTREC 1-800-424-9300/703-527-3887
Supplier information	Universal Well Services, Inc. 18360 Technology Drive Meadville, PA 16335 US

2. Hazards Identification

Emergency overview	Harmful by inhalation and in contact with skin. Prolonged exposure may cause chronic effects. Components of the product may be absorbed into the body by inhalation, ingestion and through the skin.
OSHA regulatory status	This product is considered hazardous under 29 CFR 1910.1200 (Hazard Communication).
Potential health effects	
Routes of exposure	Skin contact. Eye contact. Inhalation.
Eyes	Toxic in contact with eyes. Do not get this material in contact with eyes.
Skin	Do not get this material in contact with skin.
Inhalation	Toxic by inhalation. Prolonged inhalation may be harmful. Do not breathe dust/fume/gas/mist/vapors/spray.
Ingestion	May cause delayed lung damage. Do not ingest. Components of the product may be absorbed into the body by ingestion.
Target organs	Kidney. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged and may cause blood damage. These effects have not been observed in humans. Blood. Central nervous system. Eyes. Liver. Lungs. Respiratory system. Skin.





Chronic effects	This product may be harmful if it is absorbed through the skin. Unconsciousness. Shortness of breath. Edema. Jaundice. Cyanosis. Liver injury may occur. Kidney injury may occur. May cause central nervous system disorder (e.g., narcosis involving a loss of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage. May cause delayed lung damage.
Signs and symptoms	Unconsciousness. Discomfort in the chest. Shortness of breath. Narcosis. Cyanosis. Decrease in motor functions. Behavioral changes. Cough. Edema. Liver enlargement. Jaundice. Proteinuria.
Potential environmental effects	May cause long-term adverse effects in the environment.

3. Composition / Information on Ingredients

Components	CAS #	Percent
Glycol Ethers	111-76-2	30 - 60

4. First Aid Measures

First aid procedures	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops or persists.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops or persists.
Inhalation	If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Get medical attention immediately.
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Do not induce vomiting without medical advice.
Notes to physician	Symptoms may be delayed.
General advice	Call a physician if symptoms develop or persist. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire Fighting Measures

Flammable properties	Combustible by OSHA criteria. Containers may explode when heated. Runoff to sewer may cause fire or explosion hazard.
Extinguishing media	
Suitable extinguishing media	Water. Alcohol foam. Dry chemical. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use a solid water stream as it may scatter and spread fire.
Protection of firefighters	
Specific hazards arising from the chemical	Fire may produce irritating, corrosive and/or toxic gases.



**Protective equipment and precautions for firefighters**

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. Withdraw immediately in case of rising sound from venting safety devices or any discoloration of tanks due to fire. Move containers from fire area if you can do it without risk. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn. Use water spray to cool unopened containers. Cool containers with flooding quantities of water until well after fire is out.

6. Accidental Release Measures**Personal precautions**

Fully encapsulating, vapor protective clothing should be worn for spills and leaks with no fire. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering. Keep unnecessary personnel away. Stay upwind. Keep out of low areas.

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Should not be released into the environment.

Large Spills: Dike far ahead of liquid spill for later disposal. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. After removal flush contaminated area thoroughly with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

Never return spills in original containers for re-use.

7. Handling and Storage**Handling**

Use only with adequate ventilation. Wash thoroughly after handling. Avoid release to the environment. Avoid prolonged exposure.

Storage

Store in a closed container away from incompatible materials. Store in accordance with local/regional/national/international regulation.

8. Exposure Controls / Personal Protection**Exposure limits****ACGIH****Components****CAS #****TWA****STEL****Ceiling**

Glycol Ethers

111-76-2

20 ppm

Not established

Not established

OSHA**Components****CAS #****TWA****STEL****Ceiling**

Glycol Ethers

111-76-2

50 ppm

Not established

Not established





Engineering controls	Provide adequate ventilation.
Personal protective equipment	
Eye / face protection	Wear chemical goggles. Face-shield.
Skin protection	Wear chemical protective equipment that is specifically recommended by the manufacturer. It may provide little or no thermal protection. Protective gloves. Impervious gloves. Wear suitable protective clothing.
Respiratory protection	Wear positive pressure self-contained breathing apparatus (SCBA). When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
General hygiene considerations	Do not get this material in contact with eyes. Do not get this material in contact with skin. When using do not eat or drink. Keep away from food and drink. Handle in accordance with good industrial hygiene and safety practice. Wash hands after handling and before eating.

9. Physical & Chemical Properties

Appearance	Liquid.
Color	clear, yellow or orange
Odor	None known.
Odor threshold	Not available
Physical state	Liquid.
Form	Liquid.
pH	6.5 - 7.5
Melting point	-34.6 °F (-37.38 °C) estimated
Freezing point	Not available
Boiling point	278.6 °F (137 °C) estimated
Flash point	200 °F (93.3 °C)
Evaporation rate	Not available
Flammability	Not available.
Flammability limits in air, upper, % by volume	Not available
Flammability limits in air, lower, % by volume	Not available
Vapor pressure	Not available
Vapor density	Not available
Specific gravity	1.035 - 1.065
Relative density	1.0499 g/cm ³ estimated
Solubility (water)	Not available
Partition coefficient (n-octanol/water)	Not available
Auto-ignition temperature	446 °F (230 °C) estimated
Decomposition temperature	Not available
VOC	23.08 % estimated





10. Chemical Stability & Reactivity Information

Chemical stability	Stable at normal conditions.
Conditions to avoid	Heat, flames and sparks.
Incompatible materials	May form explosive mixtures with air. Strong oxidizing agents. Caustics.
Possibility of hazardous reactions	Hazardous polymerization does not occur.

11. Toxicological Information

Acute effects	Acute LD50: 2001 mg/kg estimated, Rat, Oral Acute LD50: 953 mg/kg estimated, Rat, Dermal Acute LC50: 10 mg/l/4h estimated, Rat, Inhalation
Component analysis - LD50	
Toxicology Data - Selected LD50s and LC50s	
Glycol Ethers	111-76-2 Inhalation LC50 Rat: 2.21 mg/L/4H; Inhalation LC50 Rat:450 ppm/4H; Oral LD50 Rat:470 mg/kg; Dermal LD50 Rat:2270 mg/kg; Dermal LD50 Rabbit:220 mg/kg
Sensitization	Not expected to be hazardous by OSHA criteria.
Local effects	Liver toxicity. Blood disorder may occur after ingestion.
Chronic effects	Hazardous by OSHA criteria. This product may be harmful if it is absorbed through the skin. Repeated absorption may cause disorder of central nervous system, liver, kidneys and blood. Prolonged or repeated exposure may cause lung injury. Prolonged exposure may cause chronic effects. 2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Subchronic effects	Kidney injury may occur. Blood disorder may occur after ingestion. Blood disorder may occur after prolonged inhalation. Blood disorder may occur after prolonged skin contact.
Carcinogenicity	Not expected to be hazardous by OSHA criteria.
ACGIH - Threshold Limits Values - Carcinogens	
Glycol Ethers	111-76-2 A3 - Confirmed animal carcinogen with unknown relevance to humans
Neurological effects	Hazardous by OSHA criteria.
Further information	Symptoms may be delayed.

12. Ecological Information

Ecotoxicity	LC50 1889 mg/L estimated, Fish, 96.00 Hours, EC50 215 mg/L estimated, Daphnia, 48.00 Hours, Components of this product have been identified as having potential environmental concerns.
Ecotoxicity - Freshwater Fish Species Data	
Glycol Ethers	111-76-2 96 Hr LC50 Lepomis macrochirus: 1490 mg/L [static]
Ecotoxicity - Water Flea Data	
Glycol Ethers	111-76-2 24 Hr EC50 water flea: 1720 mg/L; 24 Hr LC50 Daphnia magna: 1698-1940 mg/L
Environmental effects	
Ecotoxicity - Freshwater Fish Species Data	
Glycol Ethers	111-76-2 96 Hr LC50 Lepomis macrochirus: 1490 mg/L [static]
Ecotoxicity - Water Flea Data	
Glycol Ethers	111-76-2 24 Hr EC50 water flea: 1720 mg/L; 24 Hr LC50 Daphnia magna: 1698-1940 mg/L





13. Disposal Considerations

Disposal instructions

Do not allow this material to drain into sewers/water supplies. This product, in its present state, when discarded or disposed of, is not a hazardous waste according to Federal regulations (40 CFR 261.4 (b)(4)). Under RCRA, it is the responsibility of the user of the product to determine, at the time of disposal, whether the product meets RCRA criteria for hazardous waste. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Not regulated as hazardous goods.

Department of Transportation (DOT) Requirements**Bulk**

Not regulated as hazardous goods.

Department of Transportation (DOT) Requirements

Not regulated as dangerous goods.

Canadian Transportation of Dangerous Goods (TDG) Requirements

Not regulated as hazardous goods.

IMDG

Not regulated as hazardous goods.

IATA

Not regulated as hazardous goods.

15. Regulatory Information

Labelling**Contains**

Glycol Ethers

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

U.S. - CERCLA/SARA - Section 313 - Emission Reporting

Glycol Ethers	111-76-2	1.0 % de minimis concentration (applies to R-(OCH ₂ CH ₂) _n -OR', where n = 1,2, or 3, R=alkyl C7 or less, or R = phenyl or alkyl substituted phenyl, R' = H or alkyl C7 or less, or OR' consisting of carboxylic acid ester, sulfate, phosphate, nitrate, or sulfonate, Chemical Category N230)
---------------	----------	--

U.S. - FDA - Direct Food Additives

Glycol Ethers	111-76-2	21 CFR 173.315
---------------	----------	----------------

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

CERCLA (Superfund) reportable quantity

EB-Butyl Cellosolve: 1.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)**Hazard categories**

Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No





Section 302 extremely hazardous substance No
Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

International regulations**Canada - WHMIS - Ingredient Disclosure List**

Glycol Ethers 111-76-2 1 %

State regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

U.S. - Massachusetts - Right To Know List

Glycol Ethers 111-76-2 Present

U.S. - Minnesota - Hazardous Substance List

Glycol Ethers 111-76-2 Skin

U.S. - New Jersey - Right to Know Hazardous Substance List

Glycol Ethers 111-76-2 sn 0275

U.S. - Pennsylvania - RTK (Right to Know) List

Glycol Ethers 111-76-2 Present

U.S. - Rhode Island - Hazardous Substance List

Glycol Ethers 111-76-2 Toxic (skin)

U.S. - Texas - Effects Screening Levels - Long Term

Glycol Ethers 111-76-2 5 ppb ESL; 24 µg/m3 ESL

U.S. - Texas - Effects Screening Levels - Short Term

Glycol Ethers 111-76-2 50 ppb ESL; 240 µg/m3 ESL

16. Other Information**HMIS® ratings**

Health: 2*
Flammability: 1
Physical hazard: 0

NFPA ratings

Health: 2
Flammability: 1
Instability: 0





Prepared by

Amanda L. Ruston
4420 South Flores Road
Elmendorf, Texas 78112
210-626-0850

Disclaimer

THIS PRODUCT'S HEALTH AND SAFETY INFORMATION IS PROVIDED TO ASSIST OUR CUSTOMERS IN ASSESSING COMPLIANCE WITH HEALTH, SAFETY AND ENVIRONMENTAL REGULATIONS. THE INFORMATION CONTAINED HEREIN IS BASED ON DATA AVAILABLE TO US, AND IS BELIEVED TO BE ACCURATE, ALTHOUGH NO GUARANTEE OR WARRANTY IS PROVIDED OR IMPLIED BY THE COMPANY IN THIS RESPECT. SINCE THE USE OF THIS PRODUCT IS WITHIN THE EXCLUSIVE CONTROL OF THE USER, IT IS THE USER'S RESPONSIBILITY TO DETERMINE THE CONDITIONS OF SAFE USE. SUCH CONDITIONS MUST COMPLY WITH ALL GOVERNMENTAL REGULATIONS.

MSDS sections updated

Product and Company Identification: Product and Company Identification

